PRODUCT INFORMATION

REGUPOL EVERROLL ALPINE SF



Product:
tile product made of PUR-bonded EPDM-granulates, with 100 % EPDM colour content

Application Areas:
mountain and base stations

Features:
durable, sustainable, de-icing salt resistant, weatherproof, non-slip, quickly laid, trafficable, suitable for laying on grids

Thickness:
22 mm

Standard Dimension:
1,000 x 500 mm, dummy joint at 500 mm

Weight:
approx. 26.4 kg/m²

Slip Resistance:
R 10 based on DIN 51130 (02.2014) and ASR A1.5/1,2

Impact Resistance:
> 21 Nm based on EN 14904 / EN 1517

Force Reduction:
up to 23 % based on EN 14904 / EN 14808

Fire Classificatin :
C_{fl}-s1 based on EN 13501-1:2010-01 / EN9239-1:2010-11

Salt Water Resistance:
resistant based on DIN EN ISO 175

Colours:
two colours, individual colours available on request

Further technical data is available on request.

REGUPOL everroll alpine SF



Dekor 1 [5103|5109*]



Dekor 2 [5108|5102*]

* = increased light fastness only when used indoors

Deviations from the colours shown are possible due to production batches and brochure print.

We reserve the right to make changes to the technical data. The test results and specified values are subject to a tolerance of +/- 10 %. Crucial for the up-to-date data is the information on our homepage www.regupol.com.